

## SERIE GMC CONTACTORES



### Application

GMC series AC Contactor is suitable for using in the circuits up to the rated voltage 660V AC 50Hz or 60Hz, rated current up to 95A, for making, breaking, frequently starting & controlling the AC motor. Combined with the auxiliary contact block, delay timer & machine-interlocking device etc, it becomes the delay contactor, mechanical interlocking contactor, star-delta starter. With the thermal overload relay, it is combined into the electromagnetic starter. The Contactor is produced according to IEC60947-4.



### Specifications

Type	AC1 duty	AC3 duty				Life time (x 10 <sup>4</sup> )		Aux. contact
		200~240V	380~440V	500~550V	690V	Electrical	Mechanical	
GMC-9	20A	2.5kW 11A	5kW 9A	4kW 7A	4kW 5A	250	2500	1NO1NC
GMC-12	20A	3.5kW 13A	5.5kW 12A	7.5kW 12A	7.5kW 9A	250	2500	
GMC-18	25A	4.5kW 18A	7.5kW 18A	7.5kW 13A	7.5kW 9A	250	2500	
GMC-22	32A	5.5kW 22A	11kW 22A	15kW 22A	15kW 18A	250	2500	
GMC-32	50A	7.5kW 32A	15kW 32A	18.5kW 28A	18.5kW 21A	200	1500	2NO2NC
GMC-40	60A	11kW 40A	18.5kW 40A	22kW 32A	22kW 25A	200	1500	
GMC-50	80A	15kW 55A	22kW 50A	30kW 43A	30kW 33A	200	1000	
GMC-65	100A	18kW 65A	30kW 65A	37kW 60A	37kW 47A	200	1000	
GMC-75	110A	22kW 75A	37kW 75A	45kW 64A	45kW 47A	200	1000	
GMC-85	135A	25kW 85A	45kW 85A	45kW 75A	45kW 52A	200	1000	